

DATASHEET

CRIC



GENERAL

Art.Nr:	H-280-SW
GTIN:	8053841302088
Customs tariff number:	76169990

Standards:	EN 12278:2007, EN 12841:2006/B, EN 567:2013
Net weight:	0.18 kg
Gross weight:	0.00 kg

DATASHEET

CRIC

Multifunctional ascender with pulley for rope access and rescue. Robust, functional and intuitive, it can be used in four different ways: as an ascender, pulley, rope clamp / pulley or retrieval pulley.

Main features:

- Its versatility, compactness and ease of use reduce the time, material and space required during maneuvers to a minimum;
- enables ascent on a rope in accordance with the EN 567 / EN 12841-B standards (ascent mode);
- can be used as a simple rope pulley for lifting or moving a load in accordance with EN 12278 (rope pulley mode);
- the integrated ball-bearing rope pulley can be used directly to facilitate ascent on a rope or to lift a person without the aid of additional connecting elements (rope clamp / rope pulley mode);
- enables the direct recovery of a load, the creation of pulley blocks and the lifting or self-lifting of a person (recovery mode);
- in pulley mode, the rope can slide freely in both directions, while in recovery mode it can slide freely in one direction and locks in the other;
- in retrieval mode, the retrieved load can be lowered by operating the special lanyard connected to the device base;
- the ergonomic opening by means of the intuitive button allows quick installation on the rope in the desired mode, even with gloves or in adverse conditions;
- equipped with a toothed steel cam that protects the rope from wear, but also locks it effectively. The cam also has two grooves to reduce the

FEATURES

Colour:	Black
Minimum compatible rope diameter:	12.00 mm
Maximum compatible rope diameter:	8.00 mm
Min. temperature:	-12 °C
Max. temperature:	40 °C
Working Load Limit:	100 kg
Hot forged:	No
Hard coated:	No
Ascender type:	hand_ascenders

DIMENSIONS

Min. rope diameter / EN 12841:	10 mm
Max. rope diameter / EN 12841:	12 mm
Min. rope diameter / EN 567:	8 mm
Max. rope diameter / EN 567:	12 mm
Max. rope diameter / EN 12278:	11 mm

MATERIAL

Material:	Aluminium, Steel
-----------	------------------

DATASHEET

CRIC

accumulation of mud and maintain effective locking of the rope in all conditions (muddy rope, frozen, etc.).