

DATASHEET

K-ADVANCE SHELL



GENERAL

Art.Nr:	H-317	Standards:	EN 12275:2013, EN 12275:2013/K, EN 362:2004, EN 362:2004/A/T, UIAA 121
GTIN:	8056734836196	Net weight:	0.13 kg
E-class number:	40-21-07-12	Gross weight:	0.17 kg
Customs tariff number:	76169990		

DATASHEET

K-ADVANCE SHELL

Hot-forged light alloy double gate connector, ideal as a lanyard terminal.

Main features:

- ergonomic shape for an optimal handling, opening system that allows to clip and unclip into protections using one hand;
- double gate automatic locking, extremely quick and safe;
- large clearance for hooking onto big diameter wires;
- catch-free nose to avoid snagging when clipping and unclipping;
- with stainless steel wear-proof protection, for a enhanced resistance to abrasion on wire cables.

FEATURES

Colour:	Black
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	25 mm
MBS MAJOR AXIS:	30 kN
MBS GATE OPEN:	12 kN
MBS MINOR AXIS:	12 kN
Form fit:	Key Lock
Carabiner type:	Type K (EN 12275: 2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-35 °C
Max. temperature:	45 °C
Standard ANSI:	No
Standard CSA:	No
UIAA compliance:	Yes
Anti-twist device:	Yes
Hot forged:	No
Hard coated:	No
Locking mechanism:	Palm Squeeze

DIMENSIONS

Size:	One Size
Product length:	13.50 cm

DATASHEET

K-ADVANCE SHELL

Product width: 7.00 cm

MATERIAL

Material: Aluminium
