

DATASHEET

K-ADVANCE SHELL



GENERAL

Art.Nr:	H-554-820-DL	Standards:	EN 12275:2013, EN 362:2004
GTIN:	8056734832105	Net weight:	0.13 kg
E-class number:	40-21-07-12	Gross weight:	0.17 kg
Customs tariff number:	76169990		

DATASHEET

K-ADVANCE SHELL

Hot-forged light alloy double gate connector, ideal as a lanyard terminal.

Main features:

- ergonomic shape for an optimal handling, opening system that allows to clip and unclip into protections using one hand;
- double gate automatic locking, extremely quick and safe;
- large clearance for hooking onto big diameter wires;
- catch-free nose to avoid snagging when clipping and unclipping;
- with stainless steel wear-proof protection, for a enhanced resistance to abrasion on wire cables.

FEATURES

Colour:	Grey, Orange
Swivel:	No
Gate opening:	25 kN
MBS MAJOR AXIS:	30 kN
MBS GATE OPEN:	12 kN
MBS MINOR AXIS:	12 kN
Form fit:	Key Lock
Carabiner type:	Type K (EN 12275: 2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-35 °C
Max. temperature:	60 °C
Anti-twist device:	Yes
Individually tested:	Yes
100% quality control:	Yes
Hot forged:	No
Hard coated:	No
Locking mechanism:	Palm Squeeze

DIMENSIONS

Size:	One Size
Product length:	135.00 mm
Product width:	70.00 mm

MATERIAL

DATASHEET

K-ADVANCE SHELL

Material:

Aluminium, Stainless
Steel
