

DATASHEET

PEANUT Y



GENERAL

Art.Nr:	HSG-022-1,8-3	Standards:	DIN 19427:2017,EN 360:2002,GS-PS-12: 2019,RFU PPE-R/11. 060,RFU PPE-R/11. 085,RFU PPE-R/11. 124
GTIN:	4030281182047	Net weight:	3.14 kg
E-class number:	40-02-01-03	Gross weight:	3.14 kg
Customs tariff number:	84798997		

DATASHEET

PEANUT Y

The compact connecting device PEANUT Y with FS90 ST karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the fall height is extremely low. The karabiner with an opening width of 59 mm can be used variably and is extremely robust. The lanyard is perfectly suited for continuous, reciprocal securing - even at lower heights. The PEANUT Y is edge-suitable and thus also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 1.8 m long arms, the PEANUT Y is ideal for securing in aerial work platforms. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap fall arrester has been released and provides additional safety.

FEATURES

Colour:	Black, Grey, Orange
---------	---------------------

Edge approved:	Yes
----------------	-----

Maximum lifetime:	10 years
-------------------	----------

Maximum number of persons:	1
----------------------------	---

Minimum user weight:	50.00 kg
----------------------	----------

Maximum user weight vertical:	135.00 kg
-------------------------------	-----------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

DIMENSIONS

Rope length:	1.80 m
--------------	--------

MATERIAL

Material:	Polyester, Polyamide, Steel, Aluminium
-----------	--