

TM 6

Safety tripod on wheels

EN 795/B, CEN/TS 16415



Aluminium tripod on the wheels TM 6 is a component of personal protective equipment against falls from height. Safety tripod TM 6 has been tested in according to EN 795 and TS 16415 as a transportable temporary anchorage type B. Tripod has to be used in conjunction with fall arrest equipment. Tripod TM 6 provides protection for max. two people in any case. Tripod TM 6 is designed to use with RUP 502-A / 503 and CRW 300 rescue lifting devices. This is recommended that TM 6 should be transported and installed by minimum two people.



**VIDEO
PRODUCT PRESENTATION**
<https://vimeo.com/328122383>

SPECIAL FEATURES



Protection for 2 users

AL

Made of aluminium



Suitable for explosion-hazard zones

PARAMETERS

Height	169 cm
Mounting hole diameter Ø	158 mm
Leg spacing	140 mm
Weight of tripod	34 kg
Transport dimensions	200 x 47 x 47 mm
Max. number of users for lifting and lowering	2

LEGS

Material	aluminium
----------	-----------

HEAD

Material	aluminium alloy
----------	-----------------

Finishing	powdercoat
Number of anchorage points	3

FEET

Material	aluminium
----------	-----------

CHAIN

Material	galvanized steel
----------	------------------

VARIANTS

	ref. no.
	AT008

PROTEKT

PROTEKT Grzegorz Laszkiewicz Spolka z o.o. Starorudzka 9, 93-403 Lodz, POLAND
KRS: 0001009727 | REGON: 524047958 | NIP: 7292747932

WWW.PROTEKT.PL

EXPORT SALES DEPARTMENT Skromna 6, 93-405 Lodz, POLAND
Phone: +48 42 29 29 500, export@protekt.com.pl, Fax +48 42 680-20-93

TM 6

Safety tripod on wheels

PHOTOS 360 (ROTATING)

