

DATASHEET

OBX BGL



GENERAL

Art.Nr:	H-400-BGL	Standards:	EN 12275:2013, EN 12275:2013/B, EN 362:2004, EN 362:2004/B
GTIN:	8053841303023	Net weight:	0.08 kg
E-class number:	40-21-07-12	Gross weight:	0.08 kg
Customs tariff number:	76169990		

DATASHEET

OBX BGL

Hot-forged light alloy oval connector with Brilock gate and ACL system. Ideal for critical and vibration-prone connections (e.g. descender installed on the harness, construction of anchors etc.).

Main features:

- equipped with the Brilock closure system which combines the ease of use of a screw gate with additional security of an automatic lock;
- in the Neutral mode the connector is closed and the sleeve is free to rotate on itself without the lever opening and thus avoiding the risk of accidental opening due to vibrations, rubbing, impacts etc.
- in the Open mode the sleeve remains open to facilitate the performance of manoeuvres;
- oval shape for optimal positioning of devices and ropes;
- ergonomic shape which enables a good opening of the lever and improves handling;
- equipped with the ACL system which allows it to be attached to the harnesses belay loop, maintaining the correct alignment between the carabiner and the device even during the most demanding manoeuvres;
- reinforced contact areas for better rope sliding and resistance to wear and tear;
- the line between the nose and the internal part of the connector is smooth and facilitates insertion and/or disconnection from anchors, tools and ropes;
- catch-free closure.

FEATURES

Colour:	Orange, Grey
Gate opening:	22 mm
MBS MAJOR AXIS:	24 kN
MBS GATE OPEN:	7 kN
Form fit:	Key Lock
Carabiner type:	Type T (EN 12275: 2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-30 °C
Max. temperature:	-50 °C
UIAA compliance:	Yes
Anti-twist device:	Yes
Individually tested:	Yes
Hot forged:	Yes
Locking mechanism:	Brilock

DIMENSIONS

Product length:	112.00 mm
Product width:	65.00 mm

MATERIAL

Material:	Aluminium
-----------	-----------