

DATASHEET

EASY RESCUE



GENERAL

Art.Nr:	H-278
GTIN:	8056734835397
Customs tariff number:	76169990

Standards:	EN 12278:2007, EN 1909:2004, EN 795:2012/B
Net weight:	0.10 kg
Gross weight:	0.10 kg

DATASHEET

EASY RESCUE

Combined anchor and pulley for evacuation from cable cars and chair lifts, it allows evacuation by allowing rescuers to be lowered along the cable, or when the underlying terrain permits it, to allow the unloaded pulley to run down the cable to the desired position and then use it as a winch and lower anchor.

Main features:

- for use on cables \varnothing 20 ÷ 60 mm max and inclination $\pm 50^\circ$ max;
- double gate opening for a higher safety during the use;
- lightweight and well balanced, it can be used with only one hand;
- high breaking strength thanks to the connector's structure;
- safety pulley in the centre that activates in case of extra load;
- upper attachment point that allows to slide along the cable without any interference from the rope;
- side ears allowing a wider control capacity on the cable.

FEATURES

Colour:	Black, Grey, Silver
Number of rolls:	2
Attachment points top:	1
Attachment points bottom:	1
Bearings:	Self-lubricating bushings
Maximum lifetime:	30 years
Maximum compatible rope diameter:	60.00 mm
Minimum tensile strength:	28.00 kN
Minimum temperature:	-30 °C
Maximum temperature:	40 °C
Backstop:	No
Working load limit in kn:	5 kN

MATERIAL

Material:	Polyamide, Aluminium, Stainless Steel
-----------	---------------------------------------