

DATASHEET

NANOLINK FLEX Y



GENERAL

Art.Nr:	L-0960-0-180
GTIN:	4030281319269
E-class number:	40-21-08-10
Customs tariff number:	56090000

Net weight:	2.59 kg
Gross weight:	2.59 kg

DATASHEET

NANOLINK FLEX Y

The NANOLINK Lanyard Series sets a new benchmark in fall protection and has been developed for demanding use across all industries. Its compact, ergonomic energy absorber reliably protects users from 50 to 150 kg, closing a critical safety gap that many conventional lanyards leave open. Highly abrasion-resistant materials ensure long-lasting durability even in harsh environments. Multiple variants with different connector options according to EN 362 allow flexible adaptation to individual requirements. NANOLINK combines freedom of movement, robustness, and uncompromising safety – for professionals who rely on their equipment at every height.

FEATURES

Colour:	Orange, Black, Grey
Fallindicator:	Yes
Impact force:	6.00 kN
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Rescue loop:	No
Connector:	WITHOUT

DIMENSIONS

length_lanyard:	1.80 m
Lanyard rope diameter:	25.00 mm
Product length:	1.80 m

MATERIAL

Material:	Dyneema, Polyester, Steel, Aluminium
-----------	--------------------------------------