

DATASHEET

OBX TGL



GENERAL

Art.Nr:	H-400-TGL	Standards:	EN 12275:2013,EN 12275:2013/B,EN 362:2004,EN 362:2004/B
GTIN:	8053841302712	Net weight:	0.08 kg
E-class number:	40-21-07-12	Gross weight:	0.08 kg
Customs tariff number:	76169990		

DATASHEET

OBX TGL

Hot-forged light alloy oval connector with triplex gate and ACL system. Designed for placing wide-section devices (e.g., pulleys, ascenders, fall arrest devices etc.).

Main features:

- oval shape for optimal positioning of devices and ropes;
- ergonomic shape which enables a good opening of the lever and improves handling;
- equipped with the ACL system which allows it to be attached to the harnesses belay loop, maintaining the correct alignment between the carabiner and the device even during the most demanding manoeuvres;
- reinforced contact areas for better rope sliding and resistance to wear and tear;
- the line between the nose and the internal part of the connector is smooth and facilitates insertion and/or disconnection from anchors, tools and ropes;
- catch-free closure.

FEATURES

Colour:	Grey, Orange
Gate opening:	24 mm
MBS MAJOR AXIS:	24 kN
Form fit:	Key Lock
Carabiner type:	Type T (EN 12275: 2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-30 °C
Max. temperature:	50 °C
UIAA compliance:	Yes
Anti-twist device:	Yes
Individually tested:	Yes
Hot forged:	Yes
Locking mechanism:	Trilock

DIMENSIONS

Product length:	112.00 mm
Product width:	65.00 mm

MATERIAL

Material:	Aluminium
-----------	-----------