

DATASHEET

OBX SGB



GENERAL

Art.Nr:	H-400-SGB	Standards:	EN 12275:2013, EN 12275:2013/B, EN 362:2004, EN 362:2004/B
GTIN:	8053841303467	Net weight:	0.08 kg
E-class number:	40-21-07-12	Gross weight:	0.08 kg
Customs tariff number:	76169990		

DATASHEET

OBX SGB

Hot-forged light alloy oval screw gate carabiner with captive bar. Ideal for racking gear and for rigging in mountaineering and aid climbing rope manoeuvres.

Main features:

- oval shape for optimal positioning of devices and ropes;
- ergonomic shape which enables a good opening of the lever and improves handling;
- reinforced contact areas for better rope sliding and resistance to wear and tear;
- the line between the nose and the internal part of the connector is smooth and facilitates insertion and/or disconnection from anchors, tools and ropes;
- catch-free closure.

FEATURES

Colour:	Grey, Orange
Swivel:	No
Fallindicator:	No
Gate opening:	22 mm
MBS MAJOR AXIS:	24 kN
MBS GATE OPEN:	7 kN
Form fit:	Key Lock
Carabiner type:	Type T (EN 12275: 2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-35 °C
Max. temperature:	45 °C
Standard ANSI:	No
UIAA compliance:	Yes
Anti-twist device:	Yes
Individually tested:	Yes
100% quality control:	Yes
Hot forged:	Yes
Hard coated:	No
Locking mechanism:	Screwgate

DIMENSIONS

Product length:	11.20 cm
Product width:	6.50 cm

MATERIAL

DATASHEET

OBX SGB

Material: Aluminium
