

DATASHEET

PILLAR STEEL TG



GENERAL

Art.Nr:	H-287-TG	Standards:	EN 12275:2013, EN 362:2004, EN 362:2004/M
GTIN:	8056734830439	Net weight:	0.19 kg
E-class number:	40-21-07-12	Gross weight:	0.23 kg
Customs tariff number:	73269098		

DATASHEET

PILLAR STEEL TG

Galvanised-steel oval connector with triplex twist-lock gate, ideal in harsh environments and particularly recommended to set up anchors or for use with large-section devices (e.g. pulleys, ascenders and mobile fall arresters, etc.).

FEATURES

Colour:	Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	22 mm
MBS MAJOR AXIS:	30 kN
MBS GATE OPEN:	10 kN
MBS MINOR AXIS:	15 kN
Form fit:	Key Lock
Carabiner type:	Type M (EN 362: 2004)
Maximum lifetime:	30 years
Min. temperature:	-35 °C
Max. temperature:	45 °C
Standard ANSI:	No
UIAA compliance:	No
Anti-twist device:	No
Locking mechanism:	Trilock

MATERIAL

Material:	Steel
-----------	-------