

DATASHEET

LOOP SEP 22 KN



GENERAL

| | |
|------------------------|---------------|
| Art.Nr: | L-0398-1,35 |
| GTIN: | 4030281088622 |
| E-class number: | 40-02-01-04 |
| Customs tariff number: | 63079098 |

| | |
|---------------|---|
| Standards: | CEN/TS 16415:2013, EN 354:2010,EN 795: 2012/B |
| Net weight: | 0.53 kg |
| Gross weight: | 0.53 kg |

DATASHEET

LOOP SEP 22 KN

LOOP SEP was specially developed for working at sharp edges. The tensile force of 22 kN and the flexible casing made from special cutproof fibres make the loop practically indestructible. The fixing is stitched conically so that the loop does not get caught at this critical point.

FEATURES

| | |
|---------|---------------|
| Colour: | Black, Purple |
|---------|---------------|

| | |
|----------------|----|
| Fallindicator: | No |
|----------------|----|

| | |
|------------|-------|
| Hand wash: | 40 °C |
|------------|-------|

| | |
|----------------|-----|
| Edge approved: | Yes |
|----------------|-----|

| | |
|-------------------|----------|
| Maximum lifetime: | 10 years |
|-------------------|----------|

| | |
|---------------------------|----------|
| Minimum tensile strength: | 22.00 kN |
|---------------------------|----------|

| | |
|----------------------|--------|
| Minimum temperature: | -35 °C |
|----------------------|--------|

| | |
|----------------------|-------|
| Maximum temperature: | 45 °C |
|----------------------|-------|

DIMENSIONS

| | |
|-----------------|--------|
| length_lanyard: | 1.35 m |
|-----------------|--------|

MATERIAL

| | |
|-----------|----------------------|
| Material: | Polyester, Aluminium |
|-----------|----------------------|