

DATASHEET

OBX TG



GENERAL

Art.Nr:	H-400-TG	Standards:	EN 12275:2013/B, EN 362:2004/B
GTIN:	8053841302705	Net weight:	0.08 kg
E-class number:	40-21-07-12	Gross weight:	0.08 kg
Customs tariff number:	76169990990001		

DATASHEET

OBX TG

Hot-forged light alloy oval connector with triplex gate. Designed for placing wide-section devices (e.g., pulleys, ascenders, fall arrest devices etc.).

Main features:

- oval shape for optimal positioning of devices and ropes;
- ergonomic shape which enables a good opening of the lever and improves handling;
- reinforced contact areas for better rope sliding and resistance to wear and tear;
- the line between the nose and the internal part of the connector is smooth and facilitates insertion and/or disconnection from anchors, tools and ropes;
- catch-free closure.

FEATURES

Colour:	Grey, Orange
Swivel:	No
Fallindicator:	No
Gate opening:	22
MBS MAJOR AXIS:	24 kN
MBS MINOR AXIS:	10 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Minimum temperature:	-30 °C
Maximum temperature:	50 °C
UIAA compliance:	Yes
Anti-twist device:	No
Individually tested:	Yes
100% quality control:	Yes
Hot forged:	Yes
Hard coated:	No
Locking mechanism:	Trilock

DIMENSIONS

Product length:	11.24 cm
Product width:	6.55 cm

MATERIAL

Material:	Aluminium
-----------	-----------

DATASHEET

OBX TG

