

DATASHEET

TONDO SG



GENERAL

Art.Nr:	H-6034-121-SG	Standards:	EN 12275:2013,EN 362:2004
GTIN:	8053841307939	Net weight:	0.07 kg
E-class number:	40-21-07-12	Gross weight:	0.12 kg
Customs tariff number:	76169990		

DATASHEET

TONDO SG

HMS screw-lock carabiner made from hot-forged light alloy for connecting different devices and for safe use in professional rope and belay systems. The generous internal shape provides enough space for rope handling and Munter hitch applications, while the profiled design supports a strong balance between low weight and high strength. The rounded contact area helps protect ropes and connectors even during intensive use, while the catch-free closure reduces the risk of accidental snagging during operation.

FEATURES

Colour:	Yellow, Silver, Grey
Gate opening:	23 mm
MBS MAJOR AXIS:	24 kN
MBS GATE OPEN:	7 kN
MBS MINOR AXIS:	10 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275:2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-30 °C
Max. temperature:	50 °C
UIAA compliance:	Yes
Anti-twist device:	No
Individually tested:	Yes
Hot forged:	Yes
Locking mechanism:	Screwgate

DIMENSIONS

Product length:	105.00 mm
Product width:	73.00 mm
Product height:	17.00 mm

MATERIAL

Material:	Aluminium
-----------	-----------