

# TM 9-N

## Lightweight aluminum safety tripod

EN 795/B, CEN/TS 16415



The lightweight aluminum safety tripod TM9-N is an anchor point compliant with the EN795/B and TS 16415/B norms and can be used as a component of fall protection equipment. The TM9-N tripod provides protection for up to 3 people simultaneously. The TM9-N tripod consists of a powder-coated steel head, equipped with 3 ball-bearing polyamide rollers for guiding the work rope of RUP and CRW series devices. The head is also equipped with 3 anchor points located on the sides of the head. Each of these points can be used as an anchor point for fall protection equipment. One such point can only be used by 1 user at a time.

### SPECIAL FEATURES



Suitable for explosion-hazard zones



Maximum load 500 kg



Protection for max. 3 users

**AL**

Made of aluminium

### PARAMETERS

Height	209 cm
Mounting hole diameter $\emptyset$	149 mm
Leg spacing	128 mm
Weight of tripod	15.45 kg
Transport dimensions	1760 x 260 x 230 mm
Max. number of users for lifting and lowering	3
Max. weight of load to be lifted or lowered	500 kg

#### LEGS

Material aluminium

Finishing anodizing

#### HEAD

Material steel

Finishing powdercoat

Number of anchorage points 3

#### FEET

Material carbon fibre plastic

#### CHAIN

Material galvanized steel

**PROTEKT**

PROTEKT Grzegorz Laszkiewicz Spolka z o.o. Starorudzka 9, 93-403 Lodz, POLAND  
KRS: 0001009727 | REGON: 524047958 | NIP: 7292747932

WWW.PROTEKT.PL

EXPORT SALES DEPARTMENT Skromna 6, 93-405 Lodz, POLAND  
Phone: +48 42 29 29 500, export@protekt.com.pl, Fax +48 42 680-20-93

# TM 9-N

Lightweight aluminum safety tripod

## VARIANTS

ref. no.

AT011N

## ADDITIONAL PHOTOS

