

• **In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person.** Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.  
 • **PPE inspection should be conducted with the manufacturer's Instructions for Use.**  
 Download the instructions at [PETZL.COM](https://www.petzl.com).

# ASAP

## User information

Surname

Address

Identifier

## PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

**Manufacturer:** Petzl, ZI Cidex 105A - 38920 Crolles - France

				<b>N/A</b>
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

### 1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				<b>N/A</b>
---	---	--	--	------------

### 2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark.  
 Verify that the product lifetime has not been exceeded.  
 Compare with a new device to verify there are no modifications or missing elements.

### 3. Inspecting the frame

- Check the condition of the frame (marks, deformation, cracks, corrosion...).
- Check the condition of the edges of the attachment hole (marks, deformation, cracks are a sign of fall arrest).
- ASAP B71 only:  
 Check the condition of the wheel stop (marks, deformation, cracks are a sign of fall arrest).  
 Check the condition of the protective cover.

### 4. Inspecting the wheel

- Check the condition of the wheel (marks, deformation, cracks, corrosion...).
- Verify that all teeth are present and check their state of wear.  
 The wheel must not be fouled. If necessary, clean it with a brush, possibly by applying solvent with a fine brush. Avoid getting any liquid inside the mechanism.
- Check the rotation of the wheel.  
 Turn the wheel one complete revolution in both directions, making sure it rotates smoothly, without catching.

### 5. Checking the arm and the safety catch

- Check the condition of the arm (marks, deformation, cracks, corrosion...).
- Check the condition of the safety catch (marks, deformation, cracks are a sign of fall arrest).
- Check the effectiveness of the arm's return spring.

### 6. Function test: sliding on the rope

- Install the ASAP on a compatible rope, check that it slides properly on the rope in both directions.

### 7. Function test: grabbing and releasing the rope

- Install the ASAP on a compatible rope; test for correct locking by pulling downward (direction of a fall).
- After locking, verify that releasing is normally carried out.

### 8. Checking the condition of the OK TL connector

- For connector inspection, see the inspection form for your connector model at [petzl.com](https://www.petzl.com).

### Comments (detail here any defects found on the product and accomplished tasks)

#### VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date